

Get hitched to a Miller Disc!

There's a model for every size operation...every tillage need

	Disc Model	Cutting Width	Weight per foot (approx)	Blade Diameters	Gang Angles	Drawbar HP/Ft (Average condition)	Gang Shaft Size	Application**
OFFSETS	Series I		600 lbs	22", 24" & 26"	17° to 23°	10 hp	1 3/4"	Primary and secondary tillage in lighter soils, light to medium crop residue
	Rigid	7'-16'						
	2-Section	14' to 18'						
	3-Section	18' to 23'-10"			17° to 23°			
	Series II		650 lbs.	24" & 26"	17° to 23°	12 hp	1 3/4"	Primary and secondary tillage in almost any soil type, normal to heavy residue
Rigid	9' to 22'							
2-Section	16' to 22'							
3-Section	23'-10" to 26'							
	Extra Heavy Duty	9' to 18'	800 lbs	28"		15 hp	1 3/4" heat treated	
TANDEM	Series III	11'-10" to 18'	1,100 lbs.	32"	18° to 26°	20 to 22 hp	2" heat treated	Primary tillage with heavy residue; also land clearing, road construction, etc.
			1200 lbs.	36"		25 hp		
	Series VI							
	Rigid	11'-10" to 16'-9"	450 lbs.	22"	20° fixed	7-9 hp	1 3/4"	Secondary tillage with limited application to light primary
	3-Section	18'-3" to 38'-5"		24"				
	Series VII							
	Rigid	12' to 18'-2"	625 lbs.	22", 24" & 26"	15° to 20°	10-12 hp	1 3/4"	Primary tillage but also adaptable to secondary
	Fold-Up	20'-5" to 31'						

* Also available: Miller Category I in standard and reversible tandems; also Category II in small frame or wide frame models.

** Primary tillage: Disc covers 60% or more of residue on one pass
 Secondary tillage: Additional residue incorporation, seedbed preparation, herbicide incorporation, etc.

**A PRODUCT OF
 K&M Mfg. Co., Inc.**
 628 E Lake Drive
 Taylor, Texas 76574
 512-352-2588
 512-365-1272
 512-352-6061 Fax
www.hayking.com
info@hayking.com